











**Table 34**

**Miniature Lamp Guide**

											
	1 Submidjet Flanged	2 Midget Grooved	3 Miniature Screw	4 Midget Flanged	5 Index Bayonet	6 Miniature Flanged	7 Candelabra Screw	8 Miniature Bayonet	9 S.C. Bayonet	10 D.C. Bayonet	
Type	Design			Base	Bulb	Type	Design			Base	Bulb
	V	Amp	Life Hours				V	Amp	Life Hours		
PR-2	2.38	0.50	15	7	B-3½	385	28.0	0.04	50000	4	T-1¾
PR-3	3.57	0.50	15	7	B-3½	386	14.0	0.08	50000	2	T-1¾
PR-4	2.33	0.27	10	7	B-3½	387	28.0	0.04	25000	4	T-1¾
PR-6	2.47	0.30	30	7	B-3½	388	28.0	0.04	25000	2	T-1¾
PR-12	5.95	0.50	15	7	B-3½	397	10.0	0.04	5000	2	T-1¾
PR-13	4.75	0.50	15	7	B-3½	398	6.3	0.20	3000	2	T-1¾
10	2.5	0.5	3000	—	G-3½	399	28.0	0.04	25000	3	T-1¾
12	6.3	0.15	L	—	G-3½	502	5.1	0.15	100	8	G-4½
13	3.7	0.30	15	8	G-3½	515	5.0	0.115	40000	W	T-1¾
14	2.47	0.30	15	8	G-3½	555	6.3	0.25	3000	+	T-3¼
19	14.4	0.10	1000	—	G-3½	583D	5.0	0.06	100000	W	T-1¾
27	4.9	0.30	30	8	G-4¼	656	28.0	0.06	5000	+	T-3¼
37	14.0	0.09	1500	+	T-1¾	680	5.0	0.06	100000	W	T-1
40	6.3	0.15	3000	8	T-3¼	682	5.0	0.06	100000	1	T-1
43	2.5	0.50	3000	9	T-3¼	682AS15	5.0	0.06	100000	1	T-1
44	6.3	0.25	3000	9	T-3¼	683	5.0	0.06	100000	W	T-1
45	3.2	0.35	3000	9	T-3¼	683AS15	5.0	0.06	100000	W	T-1
47	6.3	0.15	3000	9	T-3¼	685	5.0	0.06	100000	1	T-1
48	2.0	0.06	1000	8	T-3¼	685AS15	5.0	0.06	100000	1	T-1
49	2.0	0.06	1000	9	T-3¼	715	5.0	0.115	40000	W	T-1
50	7.5	0.22	1000	8	G-3½	715AS15	5.0	0.115	40000	W	T-1
51	7.5	0.22	1000	9	G-3½	718	5.0	0.115	40000	1	T-1
53	14.4	0.12	1000	9	G-3½	755	6.3	0.15	50000	9	T-3¼
55	7.0	0.41	500	9	G-4½	756	14.0	0.08	50000	9	T-3¼
57	14.0	0.24	500	9	G-4½	757	28.0	0.08	7000	9	T-3¼
63	7.0	0.63	1000	10	G-6	1034	12.8	1.80	200	6	S-8
73	14.0	0.08	15000	+	T-1¾	1073	12.8	1.80	200	10	S-8
74	14.0	0.10	500	+	T-1¾	1130	6.4	2.6	200	11	S-8
82	6.5	1.05	500	11	G-6	1133	6.2	3.91	200	10	RP-11
85	28.0	0.04	7000	+	T-1¾	1141	12.8	1.44	500	10	S-8
86	6.3	0.20	20000	+	T-1¾	1143	12.5	2.00	40	10	RP-11
88	6.8	1.9	300	11	S-8	1184	5.5	6.25	100	11	RP-11
93	12.8	1.04	500	10	S-8	1251	28.0	0.23	L	10	G-6
112	1.2	0.22	5	8	GTL-3	1445	18.0	0.15	250	10	G-3½
130	6.3	0.15	3000	9	G-3½	1487	14.0	0.20	3000	—	T-3¼
131	1.3	0.10	50	8	G-3½	1488	14.0	0.15	200	9	T-3¼
158	14.0	0.24	500	+	T-3¼	1490	3.2	0.16	3000	9	T-3¼
159	6.3	0.15	10000	+	T-3¼	1493	6.5	2.80	100	11	S-8
161	14.0	0.19	4000	+	T-3¼	1619	6.7	1.90	500	10	S-8
168	14.0	0.35	1500	+	T-3¼	1630	6.5	2.75	100	—	S-8
219	6.3	0.25	L	10	G-3½	1648	8.0	2.0	1500	11	S-8
222	2.25	0.25	5	8	GTL-3	1691	28.0	0.61	1000	10	S-8
239	6.3	0.36	5000	9	T-3¼	1750D	14.0	0.08	750	W	T-1¾
240	6.3	0.36	5000	9	T-3¼	1728D	1.35	0.06	500	W	T-1¾
252	2.5	0.35	10000	4	GTL-1¾	1730D	6.0	0.04	10000	W	T-1¾
253 X	2.5	0.35	10000	2	GTL-1¾	1738	2.7	0.06	6000	W	T-1¾
259	6.3	0.25	10000	+	T-3¼	1762D	28.0	0.04	7000	W	T-1¾
261	2.5	0.35	10000	2	GTL-1¾	1764D	28.0	0.04	7000	W	T-1¾
268	2.5	0.35	10000	4	T-1¾	1767	2.5	0.20	500	3	T-1¾
334LSV	28.0	0.06	25000	2	T-1¾	1768	6	0.20	1000	3	T-1¾
305	28.0	0.56	480	10	S-8	1775	6.3	0.075	500	3	T-1¾
307	28.0	0.66	300	10	S-8	1813	14.4	0.10	1000	9	T-3¼
308	28.0	0.67	300	11	S-8	1815	14	0.20	3000	9	T-3¼
313	28.0	0.17	500	9	T-3¼	1816	13	0.33	1000	9	T-3¼
323	3.0	0.19	350	—	T-1¾	1819	28	0.04	1000	9	T-3¼
324	3.0	0.19	350	W	T-1¾	1820	28	0.10	1000	9	T-3¼
327	28.0	0.04	7000	4	T-1¾	1821	28	0.17	500	5	T-3¼
327AS15	28.0	0.04	7000	4	T-1¾	1822	36	0.10	1000	9	T-3¼
327AS25	28.0	0.04	7000	4	T-1¾	1828	37.5	0.05	3000	9	T-3¼
328	6.0	0.20	1000	4	T-1¾	1829	28	0.07	1000	9	T-3¼
330	14.0	0.08	750	4	T-1¾	1835	55.0	0.05	5000	9	T-3¼
331	1.35	0.06	500	4	T-1¾	1847	6.3	0.15	20000	9	T-3¼
334	28.0	0.04	7000	2	T-1¾	1850	5	0.09	1500	9	T-3¼
335	28.0	0.04	7000	3	T-1¾	1864	28.0	0.17	1500	9	T-3¼
336	14.0	0.08	750	2	T-1¾	1866	6.3	0.25	20000	9	T-3¼
337	6.0	0.20	1000	2	T-1¾	1869D	10.0	0.014	10000	W	T-3¼
338	2.7	0.06	6000	4	T-1¾	1891	14.0	0.24	500	9	T-3¼
342	6.0	0.04	10000	3	T-1¾	1892	14.4	0.12	1000	9	T-3¼
344	10.0	0.014	10000	4	T-1¾	1893	14.0	0.33	3000	9	T-3¼
345	6.0	0.04	10000	4	T-1¾	1895	14.0	0.27	1500	9	G-4½
346	18.0	0.04	10000	2	T-1¾	2102D	18.0	0.04	10000	W	T-1¾
349	6.3	0.20	3000	4	T-1¾	2107D	10.0	0.04	5000	W	T-1¾
370	18.0	0.04	10000	4	T-1¾	2114D	6.0	0.06	3000	W	T-1¾
373	14.0	0.08	750	3	T-1¾	2124	2.5	0.35	10000	W	GTL-1¾
375	3.0	0.015	10000	4	T-1¾	2128	3.0	0.0125	16000	W	T-1
376	28.0	0.06	25000	4	T-1¾	2158	3.0	0.015	10000	W	T-1¾
380	6.3	0.04	50000	4	T-1¾	2162D	14.0	0.100	10000	W	T-1¾
381	6.3	0.20	50000	4	T-1¾	2169	2.5	0.350	10000	W	T-1¾
382	14.0	0.08	50000	4	T-1¾	2180	6.3	0.04	50000	W	T-¾