


**Table 34 (continued)**

2181D	6.3	0.20	50000	W	T-1¾	8369	28.0	0.065	5000	—	T-1¾
2182D	14.0	0.08	50000	W	T-1¾	8610	6.3	0.20	5000	W	T-1¾
2187D	28.0	0.04	25000	W	T-1¾	8623	28.0	0.04	1000	—	T-1¾
6803	5.0	0.060	100000	W	T-¾	8627	28.0	0.04	1000	W	T-1¾
6833	5.0	0.060	100000	W	T-¾	8632	28.0	0.04	1000	—	T-1¾
6838	28.0	0.024	16000	W	T-1	8635	28.0	0.04	1000	—	T-1¾
6839	28.0	0.024	16000	1	T-1	8640	14	0.08	1000	W	T-1¾
7153	5.0	0.115	40000	W	T-¾	8666	5.0	0.08	15000	W	T-¾
7216	5	0.125	5000	W	T-1						
8362	14.0	0.08	50000	—	T-1¾						

W-Wire terminals. (-) -Not illustrated. (+) -Wedge base. L-Long life.



\*\*Bulbs are described by a letter indicating shape and a number that is an approximation of diameter expressed in eighths of an inch. For example S-8 is "S" shape, 8 eighths or 1 inch in dia.

(†) W-Wire terminals. (\*) Knurled screw.

**NEON GLOW LAMPS**

Type	Design Volts	Life Watts	Hours	** Base	Bulb
A1B	105-125	1/25	25000	W	T-2
A1C	105-125	1/10	25000	W	T-2
A1A(NE2)	105-125	1/17	25000	W	T-2
C7A(NE2D)	105-125	1/12	25000	4	T-2
A9A(NE2E)	105-125	1/12	25000	W	T-2
C2A(NE2H)	105-125	1/4	25000	W	T-2
C9A(NE2J)	105-125	1/4	25000	4	T-2
B6A(NE21)	110-125	1/4	7500	10	T-4½
B7A(NE45)	110-125	1/4	7500	8	T-4½
B9A(NE48)	110-125	1/4	7500	11	T-4½
B1A(NE51)	105-125	1/25	25000	9	T-3¼
B2A(NE51H)	105-125	1/7	25000	9	T-3¼
AIG	105-125	1/25	25000	4	T-2
AIH	105-125	1/10	25000	4	T-2
J5A(NE-30)	105-125	1	10000	0	S-11

**INDICATOR LAMPS**

Type	volts	Amps	End. Foot Candles
6PSB	6	.140	800
12PSB	12	.170	2400
24PSB	24	.073	2200
28PSB	28	.040	1900
48PSB	48	.053	1500
60PSB	60	.050	2400
120PSB	120	.025	1600

**STANDARD VOLTAGE LAMPS**

Type	Design Volts	Life Watts	Base Hours	** Style	Bulb
6S6	115	6	1500	8	S-6
6S6	145	6	1500	8	S-6
6S6/DC	120V	6	1500	8	S-6
6T4½/1	120V	6	1500	8	T-4½
7C7	115-125	7	1500	8	T-4½
10C7	115-125	10	—	8	C-7
10C7DC	115-125	10	3000	11	C-7
10S6/10	230	10	1500	8	S-6

**CM8-SERIES LAMPS**

Type	Design V.	Amps	Life Hours	Base	** Bulb
CM8-373	2.5	.35	10000	2	TL-1¾
CM8-374	2.5	.35	10000	W	TL-1¾
CM8-967	120	.02	5000	9	TL-2

W: wire terminals

**CM7-SERIES BI-PIN LAMPS**

Type	Design V.	Amps	Life Hours	** Bulb
CM7112	5.0	.021	10000	T-¾
CM7118	5.0	.115	40000	T-¾
CM7327	28.0	.04	7000	T-1¾
CM7328	6.0	.20	1000	T-1¾
CM7330	14.0	.08	750	T-1¾
CM7344	10.0	.014	10000	T-1¾
CM7367	10.0	.04	5000	T-1¾
CM7371	12.0	.04	10000	T-1¾
CM7373	14.0	.10	10000	T-1¾
CM7376	28.0	.065	5000	T-1¾
CM7377	6.3	.075	500	T-1¾
CM7380	6.3	.04	50000	T-1¾
CM7382	14.0	.08	50000	T-1¾
CM7515	5.0	.115	40000	T-1¾
CM7583	5.0	.06	100000	T-1¾
CM7628	6.0	.20	1000	T-1¾
CM7632	28.0	.04	1000	T-1¾
CM7646	14.0	.08	1000	T-1¾
CM7838	2.7	.06	6000	T-1¾
CM7945	6.0	.04	10000	T-1¾